

381167275	DATA SHEET	
Valid from: 06.06.2025	EPIC® H-BS 004 MS	

Description

- Inserts for high currents.
- High rating for currents up to 35 A
- Screw termination up to a conductor cross section of 6 mm²



Images may vary

General Characteristics

Series	H-BS 4
Version	Male
Design Size	10B
Number of Contacts	4 + PE
Wire Protection	No
Termination Methods	Screw termination: 1.5 – 6 mm²/AWG 16-10
Temperature Range	-40°C up to +125°C

Mechanical Characteristics

Cycle of mechanical operation	≥ 500
-------------------------------	-------

Electrical Characteristics

Rated voltage conductor-earth, IEC	400 V
Rated voltage conductor-conductor; IEC	690 V
Rated voltage, UL/CSA	600 V
Rated Impulse Voltage	6 kV
Rated Current, IEC	35 A
Contact Resistance	≤ 1 mΩ
Pollution degree	3

Materials and Surfaces

Contacts	Copper alloy, hard-silver plated
Insulating Body	PC
Flammability Class according to UL 94	V-0


Standard

Safety Standard	IEC 61984, IEC 60664-1
-----------------	------------------------

Creator: TODV1/BU EPIC Released: THBO1/BU EPIC	Document: DB381167276EN Version: 01	Page 1 of 3
---	--	-------------

381167275	DATA SHEET	
Valid from: 06.06.2025	EPIC® H-BS 004 MS	

Technical Drawings



381167275	DATA SHEET	
Valid from: 06.06.2025	EPIC® H-BS 004 MS	



Industrial machinery and plant engineering



Robust



Temperature-resistant

Info

Standard insert for currents up to 35A

Application range

Plant engineering
Mechanical engineering
Drive systems

Remark

Photographs are not to scale and do not represent detailed images of the respective products.

Creator: TODV1/BU EPIC Released: THB01/BU EPIC	Document: DB381167276EN Version: 01	Page 3 of 3
---	--	-------------