

1023629	DATA SHEET	
Valid from: 18.11.2022	ÖLFLEX® SOLAR XLWP [I+E]	

Application

ÖLFLEX® SOLAR XLWP [I+E] cables are weather-, UV-resistant photovoltaic cables. Thanks to optimized cable design, a constant, remarkable volume resistivity can be ensured even after long-term period in uncontaminated water. These cross-linked, halogen-free and double-insulated solar cables are suitable for permanent outdoor use and especially for the interconnection of grounded and ungrounded photovoltaic power systems. They are applicable for the connection between solar panels and as extension cable between the individual module strings or the DC/AC inverter.

Recommended use of cables for PV systems acc. to IEC 62930 and EN 50618:

Intended for use in PV installations e.g. acc. to IEC 60364-7-712 resp. HD 60364-7-712.

They are intended for permanent use outdoor and indoor, for free movable, free hanging and fixed installation.

It is also permitted to install the cables in conduit or trunking systems. Halogen free low smoke cables are intended to reduce the risks for people and goods in the event of fire, for example in buildings.

They are suitable for the application in /at equipment with protective insulation (protection class II).

They are inherently short-circuit and earth fault proof acc. to IEC 60364-5-52.

The expected period of use under normal usage conditions as specified in IEC 62930 and EN 50618 is at least 25 years.

Based on UL's Crushing, Impact Resistance and Crushing Resistance Test, ÖLFLEX® SOLAR XLWP [I+E] cables will be suitable for the installation underground if the cable is laid in a cable trench acc. to IEC 60364-5-52 resp. VDE 0100-520 or comparable standards. They are not intended for direct burial.

For underground use, installation in conduits or for open wiring even in water, where the cables can be / are exposed to uncontaminated water (salt or fresh water), the use is only permitted under the following conditions:

Submersion depth, max. 1 m

Water temperature 5 °C up to 40 °C

Additional tensile force or shearing during installation and operation has to be ruled out.

Design

Design	Sheathed single core cable acc. to IEC62930 and EN 50618
Code Designation 1x2.5 mm ² to 1x300mm ²	62930 IEC 131 H1Z2Z2-K
Certification	TÜV Rheinland certificate with No. R 50462071 (62930 IEC 131) TÜV Rheinland certificate with No. R 50345247 (H1Z2Z2-K) R 50425473 (H1Z2Z2-K)
Conductor	Fine wire strands of tinned copper acc. to IEC 60228 resp. EN 60228, conductor class 5
Core insulation	Electron beam cross-linked polyolefin co-polymer acc. to IEC 62930 and EN 50618, halogen free Colour: White
Outer sheath	Electron beam cross-linked polyolefin co-polymer acc. to IEC 62930 and EN 50618, halogen free Colour: black or blue or red

Electrical properties

Rated voltage U ₀ /U	1.0/1.0 kV AC RMS acc. to IEC 62930 and EN 50618 1.5/1.5 kV DC acc. to IEC 62930 and EN 50618
Max. permissible operating voltage	1.8 kV DC acc. to IEC 62930 and EN 50618

Creator: MAIH/PDC Released: ALTE/PDC	Document: DB1023629EN Version: 05	Page 1 of 3
---	--------------------------------------	-------------

We reserve all rights according to DIN ISO 16016.

PD 0019/05_04.18EN

1023629	DATA SHEET	
Valid from: 18.11.2022	ÖLFLEX® SOLAR XLWP [I+E]	

Test voltage	6.5 kV AC acc. to IEC 62930 and EN 50618
Current carrying capacity	IEC 62930, Table A.3 & A.4 and EN 50618, Table A.3 & A.4
DC voltage resistant in water after ageing	EN 50395, Section 9 (3 % NaCl), after water submersion @ 0.08 bar in pressure

Mechanical and thermal properties

Minimum ambient temperature fixed installation	-40 °C
Conductor temperature, fixed installation	up to +90 °C maximum conductor temperature during normal continuous operation acc. to IEC 62930 and EN 50618 up to +120 °C (maximum conductor temperature limited to 20.000 hours acc. to IEC 60216-2) acc. to IEC 62930 and EN 50618
Minimum temperature, during installation and handling	-25 °C acc. to IEC 62930 and EN 50618
Max. storage temperature	+45 °C acc. to IEC 62930 +40 °C acc. to EN 50618
Max. short circuit temperature	+250 °C (5s) acc. to IEC 62930 and EN 50618
Minimum bending radius, occasional flexing	15 x outer diameter
Minimum bending radius, stationary use	4 x outer diameter for outer diameter ≤ 8 mm 5 x outer diameter for outer diameter > 8 mm
Weather and UV resistance	acc. to IEC 62930, Appendix E and EN 50618, Appendix E
Ozone resistance	acc. to IEC 62930 and EN 50618
Halogen-free	acc. to IEC 62930 and EN 50618 acc. to IEC 60754-1 resp. EN 60754-1 and IEC 60754-2 resp. EN 60754-2
Smoke density	acc. to IEC 62930 and EN 50618 acc. to IEC 61034-2 resp. EN 61034-2
Flammability	flame retardant acc. to IEC 60332-1-2 resp. EN 60332-1-2
Acid and alkaline resistance	acc. to IEC 62930 and EN 50618 acc. to EN 60811-404 (oxalic acid and sodium hydroxide)
Underground use	acc. to UL 1277, Section 19 (Crushing Test) acc. to UL 854, Section 23 (Impact Resistance Test) acc. to UL 854, Section 24 (Crushing Resistance Test)
Presence of water	Permanent submersion AD8 acc. to IEC 62440 in unmoved water up to 1 m maximum submersion depth, and within a water temperature range from 5 °C up to 40 °C
Salt mist resistance	acc. to DIN EN 60068-2-11
Ammonia resistance	Test requirements based on EN 50618 Medium: 10 % ammonium hydroxide 7d, 23 ± 2 °C resp. 21d, 23 ± 2 °C Deviation: ± 30 %

Creator: MAIH/PDC Released: ALTE/PDC	Document: DB1023629EN Version: 05	Page 2 of 3
---	--------------------------------------	-------------

1023629	DATA SHEET	
Valid from: 18.11.2022	ÖLFLEX® SOLAR XLWP [I+E]	

CTI - Determination

acc. to IEC 60112, CTI 600

General requirements

These cables are conform to the EU-Directive 2014/35/EU (Low Voltage Directive)

Environmental information

These cables meet the substance-specific requirements of the EU Directive 2011/65/EU (RoHS).

Creator: MAIH/PDC Released: ALTE/PDC	Document: DB1023629EN Version: 05	Page 3 of 3
---	--------------------------------------	-------------

We reserve all rights according to DIN ISO 16016.

PD 0019/05_04.18EN