

0091330	DATA SHEET	
valid from: 01.01.2019	ÖLFLEX® HEAT 260 C MC	

Application

ÖLFLEX® HEAT 260 C MC cables are heat resistant cables. Besides having excellent mechanical and physical properties, ÖLFLEX® HEAT 260 C MC cables also are characterized by very good electrical values as well as outstanding resistance against oil, weather and UV- radiation. In addition these cables are resistant to water, acids, alkalis, solvents, paints, petrol and oils. They have also high dielectric strength and high abrasion resistance. The screen is a protection against electrical interference. The cables are flame retardant.

Design

Conductor	fine wire strands of nickel plated copper acc. to IEC 60228 resp. VDE 0295 class 5
Insulation	Polytetrafluoroethylene (PTFE), 5Y11 acc. to VDE 0207 part 6
Core identification code	colour coded according VDE 0293-308, with or without gn/ye ground conductor
Stranding	cores twisted together, PTFE-tape wrapping
Screen	braiding of nickel plated copper wires, coverage = 85% (nominal value)
Outer sheath	Polytetrafluoroethylene (PTFE), 5YM1 acc. to VDE 0207 part 6 colour: black, similar RAL 9005

Electrical properties at 20°C

Rated voltage	U ₀ /U: 300/500 V
Test voltage	c/c: 2500 V AC c/s: 2000 V AC

Mechanical and thermal properties

Minimum bending radius	occasional flexing: 15 x outer diameter fixed installation: 4 x outer diameter
Temperature range	fixed installation: -190°C up to +260° C max. conductor temperature for short-time: up to +300°C
Flammability	flame retardant acc. to IEC 60332-1-2
General requirements	These cables are conform to the EU-Directive 2014/35/EU (Low Voltage Directive)

Creator: LABU / PDC	Document: DB0091330EN	Page 1 of 1
Released: ALTE / PDC	Version: 03	