

Requirements from customer



Want a quote within (date): Project name: Date:

Company: Name:
Purchase:

Function: Email: Phone:

Name:
Design:

Email: Phone:

Development of existing product: New product: Replacement for competing product:

If product is to be a replacement for competing product, what is the cause:

Price: Quality: Technical characteristics: Delivery time: Problem supplier:

Total length: **meter w/tolerance**
Single purchase: **Annual consumption, meter, ca:** **Target price in Euro:**

Conductor specifications:

Aluminium conductor: Copper conductor: Tinned copper conductor: Silvered copper conductor: Unshielded: Shielded:

If shielded, how is it shielded

Individually shielded: Pair-shielded: External screened:

If shielded, what kind of screen

Aluminium tape with drain wire: Shield braiding: Spinning shield: Other kind:

If hybrid, define:

Number of conductors: Cross section: Voltage: Hybrid: Signal: Power:

Color of outer sheath: Material outer sheath: Color code conductors: Number conductors: Other:

Indoor use: Temperature range, min: Static cables: Bending radius static, mm: Torsion angle:

Outdoor use: Temperature range, max: Flexible cables: Bending radius flexing, mm: Speed, m/sec.:

Brief description of application

Physical and chemical requirements:

Test-voltage: <input type="text"/>	Oil resistant, specify: <input type="text"/>
Operating temperature: <input type="text"/>	Chemical resistant, specify: <input type="text"/>
Halogen free: <input type="text"/>	Solvents, specify: <input type="text"/>
Flame propagation: <input type="text"/>	Fire properties, specify: <input type="text"/>
UV-resistant: <input type="text"/>	Resistant to water penetration: <input type="text"/>
Armouring: <input type="text"/>	Sparks from welding: <input type="text"/>
	Mechanical stress, specify: <input type="text"/>
	Necessary Certificates / CPR / Approvals: <input type="text"/>
	Other: <input type="text"/>